

PS336

Windows®. Life without Walls™. Getac recommends Windows 7.

FULLY RUGGED 3.5" HANDHELD

- MIL-STD 810G and IP68 certified
- Microsoft Windows® Embedded Handheld 6.5
- 3.5G WWAN option
- RS232 Serial Port, USB OTG
- Field swappable long-life Li-Ion battery
- Embedded high sensitivity GPS receiver
- 5 Megapixel auto-focus camera



Windows® Embedded Handheld.

The PS336 comes with Windows Embedded Handheld 6.5, providing you with a wider range of uses and applications across utility and field service sectors.



GIS Ready.

The PS336 rugged handheld is built with an e-compass, altimeter, integrated GPS and a G-sensor accelerometer that can measure speed, vibration and rotation. These features open the door to countless application possibilities, making it ideal for GIS surveying and other GPS/mapping-based applications.



Information Capture.

With Getac Flexiconn™ technology, you can easily add new modules/caps to expand functionality including 3-in-1 HF RFID Card Reader, Long Range Bluetooth, 1D Barcode Reader.



Built to Survive™.

In addition to IP68 certification, which protects against dust and allows the unit to be water-proof up to one meter, the PS336 is independently certified to MIL-STD 810G standard, and can operate in temperatures from -22 °F to 140 °F.



Sunlight Readable Display.

The PS336 features a 3.5 inch display specifically designed for viewing in direct sunlight. The display uses a special multi-layered touch sensor that registers pressure, allowing you to keep your gloves on - perfect for using in cold or hazardous environments.



5 Megapixel Camera.

The PS336 features a built-in 5-megapixel camera with autofocus and an LED flash - perfect for GIS mapping.

GETAC PS336

Specifications



DuraTech USA Inc.
A Certified 8(a), SDB, DBE, SBE, MBE, WBE firm.
Phone: (714) 898-2171 Fax: 866-704-9132
Email: sales@DuraTechUSA.com www.DuraTechUSA.com

Ruggedness	MIL-STD 810G certified IP68 certified Drop resistant (26 drops from 6ft / 1.82m) Tumble resistant (1,000 cycles; 0.5 m / 1.6 ft)
Operating System	Windows® Embedded Handheld 6.5 Professional Windows® Embedded Handheld 6.5 Classic
Microprocessor	TI AM3715 1GHz
Memory	512MB MDDR
Storage	256MB NAND Flash and 8GB iNAND*
Expansion Slot	FlexiConn™ expansion module Micro SDHC (up to 32GB)
Display	3.5" VGA (480 x 640 pixel) 600 nits sunlight readable display Pressure sensitive touchscreen
Keypad	Nuance XT9® Soft input panel (SIP) Transcriber handwriting recognition Alpha/numeric keypad
Communications	WLAN 802.11 b/g/n Bluetooth® (v2.1 +EDR Class 2) GPS Optional 3.5G WWAN
Camera	5 Megapixel auto-focus
Special Features	E-Compass Altimeter

Included Accessories	AC adapter USB cable Hand strap Battery Stylus pen and tether
GPS Sensor Specifications	Chipset: SiRF Star IV™ Receiver type: L1 (C/A) Channels: 48 channel all-in-view tracking Update rate: 1 Hz Autonomous: 8.2 ft / 2.5 m DGPS: 6.56 ft / 2.0 m Cold start time: 35 sec average Hot start time: 1 sec average Reacquisition: 0.1 sec average
Power	Battery type: 3.7V, 5600mAh Li-Ion battery pack
Dimensions and Weight	7" x 3.5" x 1.18" (178 x 89 x 30 mm) 18.69 oz (530 g)**
Temperature	Operating temp: -22°F to 140°F (-30°C to 60°C) Storage temp: -40°F to 158°F (-40°C to 70°C) 95% RH, non-condensing
I/O Interfaces	DC x 1 USB OTG x 1 RS232 x 1 Office docking port x 1 Speaker x 1 FlexiConn™ (3-in-1 card reader, 1D barcode reader, long range Bluetooth or 13.56 MHz RFID with contactless smartcard reader)
Warranty	3 Year limited warranty standard†

Specification subject to change without notice. Battery performance will vary based on software applications, wireless settings, power management settings, LCD brightness, customized modules and environmental conditions. As with all batteries, maximum capacity decreases with time and use and may eventually need to be replaced by a Getac service provider. Battery life and charge cycles vary by use and settings. Battery life may be reduced in subzero applications.

* For storage, 1GB = 1 billion bytes; actual formatted capacity less.

** Weight is without 3G module. Weight varies by configuration and manufacturing process.

† For warranty terms and conditions visit www.getac.com

Copyright 2012, Getac, All Rights Reserved. Getac and the Getac logo are either registered trademarks or trademarks of Getac Technology Corporation in the United States and/or other countries. Microsoft and Windows are registered trademarks of Microsoft Corporation in the United States and in other countries. All other trademarks are the property of their respective owners.

V1M11Y12